



The mullion reader is a proximity 13.56 Mhz reader working with Easy Door Controller or IPassan. It sits directly on a wall without any embedded box. Its read range is up to 3 cm. Functioning :

A two-color led indicates the operating status of the reader: red to indicate the reader is in use and green when the door is controlled and give the permission to enter.

## Technical characteristics



13.56 MHz

- Dimensions (W x H x D) : 78x43x17mm
- Power supply: 12VDC (Supplied by the controller)
- Current: 100mA
- Frequency : 13.56MHz - Mifare Classic or Mifare Plus
- Reader connection <-> Controller : 2 wires / max 100m
- Read range: up to 30 mm
- Operating Temperature: -10 ° C to +50°C

## Produits associés obligatoires

### Accessoires

FD-010-051  
LOT DE 10 CARTES  
ISO 13.56 MHZ

**Disclaimer:** Whilst every effort has been made to ensure accuracy in the representation of this product, neither FDI MATELEC nor its employees, shall be liable under any circumstances to any party in respect of decisions or actions they may make as a result of using this information. In accordance with the FDI MATELEC policy of enhanced development, design and specifications are subject to change without notice.



**Disclaimer:** Whilst every effort has been made to ensure accuracy in the representation of this product, neither FDI MATELEC nor its employees, shall be liable under any circumstances to any party in respect of decisions or actions they may make as a result of using this information. In accordance with the FDI MATELEC policy of enhanced development, design and specifications are subject to change without notice.

